

**VOSGES di Moreno Beggio**  
**Magnetic Catalyzer Department**  
Via Roma, 133  
36040 - TORRI DI QUARTESOLO -  
VICENZA - ITALY

ph. +39-0444-387119 r.a.  
telefax +39-0444-264228  
mail : [estero@vosges-italia.it](mailto:estero@vosges-italia.it)  
<http://www.vosges-italia.it>

**STEPS TO BE TAKEN FOR THE CORRECT  
INSTALLATION AND PROPER PERFORMANCE OF  
VOSGES SUPER CATALYZER TRUCK AND  
TOP CALOR FOR HEAVY VEHICLES**



**NEW FUNCTIONALITY WITH THE APPLICATION  
OF MAGNETIC CATALYZER SUPER CATALYZER**

## FUEL : DIESEL

1. After checking the equipment on which the Vosges apparatus has to be mounted, to know if the heavy vehicles are always utilized on the same line/way and particularly with the same load for the uniformity of the test.
2. To verify the previous consumption of latest 6 months with the possibility to have them divided for to separate refuelling and with the indication of Km distance.
3. By the analyser, make the pollution test, in order to check the parameters of the motor vehicle. To reject the vehicle that doesn't have one crawled homogeneous.
4. Install our **Super Catalyzer** as our enclosed instructions describe and more precisely : between the fuel pump and the diesel filter in the models with pump, after diesel filter in the models with injectors pump.
5. To verify the consumption for at least following 2 months for to have the control parameter.
6. To run with the **Super Catalyzer** installed at least 5.000 Km for to consent a correct stabilisation.
7. By the analyser, make another pollution test for to have the parameters of comparison.
8. After this running-in the filter element can be substituted a longer interval.
9. The cleaning will progress slowly and it will be roughly total after about 10.000 Km (this means for trucks with significant mileage).